



Declaration of Performance

according to Regulation 305/2011 of the EUROPEAN PARLAMENT and of the COUNCIL laying down harmonized conditions for the marketing of construction products

Identify code	ST/T1/2101
Typ	Separator for light liquids Oleopator/Oleolift P Freestanding
Use	Light liquid removal from waste water to protecting drainage systems and surface water
Manufacturer	ACO Industries Tábor s.r.o., Průmyslová 1158, 39101 Sezimovo Ústí
Attestation of conformity system	System 4: The manufacturer has discovered the type of product according to the system 4 based of type testing, type calculation, tabulated values (or documentation of the product) and carried out factory-owned production control. Document No. 130621LD
Attestation of conformity system reaction to fire	System 3: The notified agency "PAVUS" (NB Nr. 1391) conducted tests on reaction to fire of the PE material, protocol No. PK1-01-18-070-E-0


The separator for light liquids is built in accordance to the Construction Products Directive 305/2011/EWG.

The following harmonized standards in the current version at the date of issue have been applied:

EN 858-1:2005	Separator systems for light liquids – part 1: construction, performance and testing, marking and quality control
EN 858-2:2003	Separator systems for light liquids – part 2: selection of nominal size, installation, operation and maintenance
EN 13501-1:2007	Classification of construction products and building their fire behavior – part 1: classification using test data from reaction to fire performance of construction products


Main features	EN 858-1	Performance
Reaction to fire	6.2.8	E
Fluid resistant	6.3.2	pass
Effectiveness	5, 6.3.1, 6.3.3-6.3.8, 6.5	pass
Capacity	6.4	pass
Durability	6.2	pass

Signed for and on behalf of the manufacturer.
Sezimovo Ústí, 6 January 2021



Libor Dočekal (R&D manager)

Information accompanying the CE marking


<p>ACO Industries Tábor s.r.o. Průmyslová 1158 39101 Sezimovo Ústí</p> <p>21</p>
<p>EN 858-1:2005</p> <p>separator systems for light liquids Oleopator/Oleolift P Freestanding class I</p> <p>Material: PE-HD Installation parts: PE-HD</p>

Overview of the CE marked separator systems for light liquids
Typ „Oleopator/Oleolift P Freestanding“

NS	Sludge trap- volume	Oil storage capacity	Total capacity Oleopator/Oleolift
	(l)	(l)	(l)
3	0	60	115
3	300	60	385/385
3	600	60	750/695
6	0	186	560
6	600	129	1140/977
6	1200	208	1990/1600
10	0	186	560
10	1000	273	1590/1490
15	0	464	1340
15	1500	464	2400
20	0	594	1540
20	2000	891	3410
30	0	654	1500
30	3000	1513	6080